

<b>现场总线 Fieldbus</b>	
现场总线协议	EtherCAT
现场总线接口	2 × RJ45
现场总线地址	由拨码开关或者主站配置 DIP switch setting or Master station configuration
<b>本地总线 Local bus</b>	
扩展能力	不支持扩展 Extension not supported
<b>IO 接口 IO interface</b>	
数字量信号 Digital signal	16DI (PNP/NPN), 16DIO(NPN 输入/NPN 输出可配置, 2 路一组配置) 16DI (PNP/NPN), 16DIO (NPN input/NPN output configurable, 2-way group configuration)
过流保护阀值 Overcurrent protection threshold	1.5A, 5ms
IO 响应时间 IO Response Time	最小 500us Min. 500us
本体 IO 点 Main IO point	有, <a href="#">详见订货数据</a> Yes, please refer to the ordering data for details
主从类别 Master Slave Category	独立的从设备 Independent slave device
接口类型 Interface type	插拔式连接器, 直插式弹簧连接 Pluggable connectors, PUSH-IN connection
<b>电源供电 Power Supply</b>	
工作电压 Working voltage	24 VDC (18...28 VDC)
电源保护 Power protection	防反接保护, 浪涌吸收 Anti reverse protection, surge absorption
接口类型 Interface type	插拔式连接器, 螺钉连接 Pluggable connectors, Screw connection
<b>一般数据 General data</b>	
工作环境温度 Operation temperature	-20~60°C
工作环境湿度 Operation humidity	5%~90%(无凝露) 5%~90% (without condensation)
海拔 Altitude	2000 米以下(80kPa) Below 2000 meters (80kPa)
防护等级 Degree of protection	IP20
尺寸 (长*宽*高) Dimensions (L * W * H)	27*94*114 (mm)
安装方式 Installation	DIN35 导轨安装 DIN35 rail installation
状态指示灯 Status indicator	电源、NET 绿色指示灯, SF 红色指示灯, IO 信号绿色指示灯 Power supply, NET green indicator light, SF red indicator light, IO signal green indicator light