

<b>本地总线 Local bus</b>	
扩展协议 Extension Bus	DH Bus
扩展接口 Extension interface	2 × RJ45 (标配 7CM 扁型网线用于集中型安装) 2 × RJ45 (Standard 7CM flat network cable for centralized installation)
扩展距离 Extension distance	总计 150 米, 模块间限长 20 米 (超 5 类网线) Total: Max. 150m; Between adjacent modules: Max. 20m (exceeding Category 5 network cable)
<b>IO 接口 IO interface</b>	
模拟量输入 Analog input	4 通道 4 channels
电压量程及过程数据 Voltage range and process data	±10V, -32000~32000 (满量程) ± 10V, -32000~32000 (full range)
电流量程及过程数据 Current range and process data	0~20mA, 0-32000 (满量程) 0~20mA, 0-32000 (full range)
精度 Accuracy	16 Bit
接口类型 Interface type	插拔式连接器, 直插式弹簧连接 Pluggable connectors, PUSH-IN connection
<b>电源供电 Power Supply</b>	
工作电压 Working voltage	24 VDC (18...28 VDC)
电源保护 Power protection	防反接保护, 浪涌吸收 Anti reverse protection, surge absorption
接口类型 Interface type	插拔式连接器, 螺钉连接 Pluggable connectors, Screw connection
<b>一般数据 General data</b>	
工作环境温度 Operation temperature	-20~60°C
工作环境湿度 Operation humidity	5%~90%(无凝露) 5%~90% (without condensation)
海拔 Altitude	2000 米以下(80kPa) Below 2000 meters (80kPa)
防护等级 Degree of protection	IP20
尺寸 (长*宽*高) Dimensions (L * W * H)	27*94*114 (mm)
安装方式 Installation	DIN35 导轨安装 DIN35 rail installation
状态指示灯 Status indicator	电源、BF 红色指示灯, SF 红色指示灯, IO 信号绿色指示灯 Power supply, BF red indicator light, SF red indicator light, IO signal green indicator light
<b>电气特性 Electrical characteristics</b>	
通道与总线之间隔离 Isolation between channels and bus	有 Yes
通道间隔离 Channel to channel isolation	有 Yes
系统电源诊断和警告 System power diagnosis and warnings	支持 Support