

| | |
|--|--|
| 现场总线 Fieldbus | |
| 现场总线协议 | CC-Link IE Field Basic |
| 现场总线接口 | 2 × RJ45 |
| 现场总线地址 | 由拨码开关或者网页设置 Set by DIP switch or webpage |
| 本地总线 Local bus | |
| 扩展协议 Extension Bus | DH Bus |
| 扩展接口 Extension interface | 1 × RJ45 (黑色) 1 × RJ45 (Black) |
| 扩展能力 Extension capability | 16 个 DFH20-DHB 模块 16 DFH20-DHB modules |
| 扩展距离 Extension distance | 总计 150 米, 模块间限长 20 米 (超 5 类网线) Total: Max. 150m; Between adjacent modules: Max. 20m (exceeding Category 5 network cable) |
| 扩展附件 Extension accessories | 终端电阻 (出厂标配) Terminal resistor (factory standard) |
| IO 接口 IO interface | |
| 数字量输入 Digital input | 16DI (PNP/NPN) |
| 数字量输出 Digital output | 16DO (NPN) |
| 过流保护阈值 Overcurrent protection threshold | 1.5A, 5ms |
| IO 响应时间 IO Response Time | 最小 2ms Min. 2ms |
| 接口类型 Interface type | 插拔式连接器, 直插式弹簧连接 Pluggable connectors, PUSH-IN connection |
| 电源供电 Power Supply | |
| 工作电压 Working voltage | 24 VDC (18...28 VDC) |
| 电源保护 Power protection | 防反接保护, 浪涌吸收 Anti reverse protection, surge absorption |
| 接口类型 Interface type | 插拔式连接器, 螺钉连接 Pluggable connectors, Screw connection |
| 一般数据 General data | |
| 工作环境温度 Operation temperature | -20~60°C |
| 工作环境湿度 Operation humidity | 5%~90%(无凝露) 5%~90% (without condensation) |
| 海拔 Altitude | 2000 米以下(80kPa) Below 2000 meters (80kPa) |
| 防护等级 Degree of protection | IP20 |
| 尺寸 (长*宽*高) Dimensions (L * W * H) | 27*104*114 (mm) |
| 安装方式 Installation | DIN35 导轨安装 DIN35 rail installation |
| 状态指示灯 Status indicator | 电源、NET 绿色指示灯, SF 红色指示灯, IO 信号绿色指示灯 Power supply, NET green indicator light, SF red indicator light, IO signal green indicator light |