



未注公差/General tolerances (mm)													0.1/10	
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'



Note:
The A&Z(H) in the name means: A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin header	Copper alloy	Sn plated
3	Spring	Stainless steel	/
2	Housing	PA66	UL94V-0
1	Cover	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	150/4	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	130/6	/
工频耐压/Withstanding Voltage(V/Min)	/	AC1500	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	28~20/ 0.2~0.5		
间距/Pitch(mm)/线数范围/Poles	2.54/N=01~24P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		



MATERIAL:	SURFACE/COLOR:
MAT NO./REV: / 00	MAT STATUS: 批量

APPD: 兰春华	2022.10.24
CHKD: 陈招	2022.10.24
DRFT: 龚徐涛	2022.10.21

NAME		DG240W-2.54-XXP-1Y-00A&Z(H)			
DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET	
200029176	CUSTOMER DRAWING	已发布	3:1	1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
00			龚徐涛	2022.10.21



DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200029176	CUSTOMER DRAWING	已发布	3:1	1/1

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing. All rights reserved for patent. 除专利号明确标注外, 其他内容均受法律保护。未经许可, 不得复制或传播。本公司保留对涉及专利、实用新型及外观设计的所有权利。