


PCB LAYOUT

F距方向公差(mm)			其他尺寸公差(mm)					—	∩	∟
≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	>150	0.05/10		
±0.10	±0.15	±0.25	±0.20	±0.30	±0.50	±0.70	±1.00	±1'		



Note: The A&Z (H) in the name means: A(H) and Z(H).

UL 额定电压/Rated Voltage/Current	600V/45A
UL 工频耐压/R.M.S withstand voltage	AC2200V/1Min
IEC 额定电压/Rated Voltage/Current	1000V/76A
额定脉冲电压/Rate Impulse Voltage(KV)	4
线径范围/Wire range(AWG/mm ²)	22-8/0.5-16
线数范围/Poles	N=03-14P
重点管控符号/Key controlled symbol	-
螺丝扭矩/Tightening torque(N.m/Lb.in)	M5.2 0.17.54
使用温度范围/Operating temperature(°C)	-40 ~ +120

5	Nut	STEEL	Zn Plated
4	Pin header	BRASS	Sn Plated
3	Screws	STEEL	Zn Plated
2	Cover	PC	UL94V-0
1	Housing	PBT	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

		MATERIAL:	SURFACE/COLOR:		
APPD: 彭敏	2024.11.25	MAT NO./REV:	/ 00	MAT STATUS: 批量	
CHKD: 曹利彬	2024.11.25	NAME: DG1450H-B-XXP-1Y-30A&Z(H)			
DRAFT: 姜民浩	2024.11.25	DRAWING NO.	TYPE	DRAWING STATUS	SCALE
		200074352	CUSTOMER DRAWING	已发布	1:1
REV	ECN	DESCRIPTION	DRAFT	DATE	SHEET
00					1/1

Transfer or duplication of this document as well as the utilization or reproduction of its contents without the written permission of DEGSON is prohibited. All rights reserved for patent.