

树脂外壳 Resin shell


 圆柱型-DCK系列
Cylindrical-DCK series


型号 Model		DCK-F12-03 NO	DCK-F18-08 NO		
NPN常开 NPN normally open					
其他 Other		[NO]:NPN 常开 [NC]:NPN Normally Open	[PO]:PNP 常开 [PO]:PNP Normally Open		
基本特点 Basic Features					
工作原理 Working principle	电感式传感器 Inductive Sensors				
外壳样式 Enclosure style	圆柱形 Cylindrical				
安装方式 Installation	齐平 Flush				
检测距离 Detection distance	3.0mm	8.0mm			
螺纹规格 Thread specification	M12	M18			
感应面材质 Sensing surface material	PBT				
检测物 Detection	金属, 液体, 粉末, 木材, 纸张, 塑料等材料 Metal, liquid powder, wood, paper, plastic and other materials				
指示灯 Light	运行状态: LED Operating status: LED				
检测距离调节 Detection distance adjustment	有 Have				
电气数据 Electrical Data					
开关模式 Switch mode	NO: 常开, NC: 常闭 NO: Normally Open, NC: Normally Closed				
输出模式 Output mode	NPN或PNP集电极开路 NPN or PNP open collector				
外部输入 External Input	无 None				
开关频率 Switching frequency	0.1kHz				
重复精度 Repeatability	5%				
迟滞(回差/应差) Hysteresis (Return/Response)	15%				
工作电压 Operating voltage	10~30V DC ±10%				
消耗电流 Current consumption	≤10mA				
残余电压 Residual voltage	≤2V				
负载电流 Load current	150mA	300mA			
漏电流 Leakage Current	<0.01mA				
绝缘电阻 Insulation resistance	电源端子与外壳之间 ≥0MΩ (500VDC) Between power terminal and housing ≥50MΩ (500VDC)				
耐压 Resistance	1000VAC (50/60Hz), 1分钟电源端子和外壳之间 1000VAC (50/60Hz), 1 minute between power terminals and case				
抗振性 Vibration resistance	10~55Hz, 振幅1.5mm, X/Y/Z轴, 各2小时 10~55Hz, amplitude 1.5mm, X/Y/Z axis, 2 hours each				
保护电路 Protection circuits	短路保护 Short-circuit protection				
环境条件 Environmental Conditions					
工作环境温度 Operating ambient temperature	-25~+75°C				
工作环境湿度 Humidity of the working environment	35~85%				
防护等级 Ingress protection	IP67				
机械数据 Mechanical Data					
连接方式 Connection	2m/3线电缆 2m/3-wire cable				
尺寸 Size	M12x56.9mm	M18x72.5mm			
材料 Material	PBT				
重量 Weight	0.05kg	0.08kg			
配件 Fittings	螺母 M12x1.0 Nut M12x1.0	螺母 M18x1.0 Nut M18x1.0			

尺寸规格 Dimensions

M12

DCK-F12-03□□



M18

DCK-F18-08□□

