

## 电缆式 Cable Type


 超远距离-DLY系列  
Ultra long distance-DLY series


型号 Model		DLY-F08-03	DLY-F12-06	DLY-N08-06	DLY-N12-10
NPN常开 NPN normally open					
其他 Other		NO:NPN 常开 NO:NPN Normally Open	NC:NPN 常闭 NC:NPN Normally Closed	PNP常开 PNP Normally Open	PNP常闭 PNP Normally Closed
基本特点 Basic Features					
工作原理 Working principle	电感式传感器 Inductive Sensors				
外壳样式 Enclosure style	圆柱形 Cylindrical				
安装方式 Installation	齐平 Flush			非齐平 Non-flush	
检测距离 Detection distance	3.0mm±10%	6.0mm±10%	6.0mm±10%	10mm±10%	
螺纹规格 Thread specification	M8	M12	M8	M12	
感应面材质 Sensing surface material	PBT				
检测物 Detection	金属感应物 Metal sensor				
指示灯 Light	运行状态: LED Operating status: LED				
检测距离调节 Detection distance adjustment	无 None				
电气数据 Electrical Data					
开关模式 Switch mode	NO: 常开, NC: 常闭 NO: Normally Open, NC: Normally Closed				
输出模式 Output mode	NPN或PNP集电极开路 NPN or PNP open collector				
外部输入 External input	无 None				
开关频率 Switching frequency	1.0kHz	0.8kHz	0.5kHz	0.4kHz	
重复精度 Repeatability	5%				
迟滞 (回差/应差) Hysteresis (Return/Response)	15%				
工作电压 Operating voltage	10~30V DC±10%				
消耗电流 Current consumption	≤10mA				
残余电压 Residual voltage	≤1.5V				
负载电流 Load current	150mA				
漏电流 Leakage Current	<0.01mA				
绝缘电阻 Insulation resistance	电源端子与外壳之间 ≥50MΩ (500VDC) Between power terminal and housing ≥50MΩ (500VDC)				
耐压 Resistance	1000VAC (50/60Hz), 1分钟电源端子和外壳之间 1000VAC (50/60Hz), 1 minute between power terminals and case	<40V	1000VAC (50/60Hz), 1分钟电源端子和外壳之间 1000VAC (50/60Hz), 1 minute between power terminals and case		
抗振性 Vibration resistance	10~55Hz, 振幅1.5mm, X/Y/Z轴, 各2小时 10~55Hz, amplitude 1.5mm, X/Y/Z axis, 2 hours each				
保护电路 Protection circuits	短路保护 Short-circuit protection				
环境条件 Environmental Conditions					
工作环境温度 Operating ambient temperature	-25~+75°C				
工作环境湿度 Humidity of the working environment	35~85%				
防护等级 Ingress protection	IP67				
机械数据 Mechanical Data					
连接方式 Connection	2m/3线电缆 2m/3-wire cable				
尺寸 Size	M8x45.0mm	M12x45.0mm	M8x44.0mm	M12x53.0mm	
材料 Material	不锈钢+PBT Stainless steel + PBT	镍铜合金+PBT Nickel copper alloy + PBT	不锈钢+PBT Stainless steel + PBT	镍铜合金+PBT Nickel copper alloy + PBT	
重量 Weight	0.012kg	0.05kg	0.012kg	0.05kg	
配件 Fittings	螺母 M8x1 Nut M8x1	螺母 M12x1 Nut M12x1	螺母 M8x1 Nut M8x1	螺母 M12x1 Nut M12x1	


## 电缆式 Cable Type

M8

DLY-F08-03 □□




DLY-N08-06 □□



M12

DLY-F12-06 □□



DLY-N12-10 □□

